

## 1. Identification

Product identifier	Toluene
Other means of identification	
Product code	R00000006800
Recommended use	Industrial chemical.
Recommended restrictions	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	

Toledo Refining Company, LLC  
1819 Woodville Road  
Oregon, OH 43616

Telephone number 419-698-6600

Emergency telephone number Chemtrec 800-424-9300

## 2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system, kidney, peripheral nervous system)
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
OSHA defined hazards	Not classified.	

### Label elements



### Signal word

Danger

### Hazard statement

Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs (central nervous system, kidney, peripheral nervous system) through prolonged or repeated exposure. Toxic to aquatic life.

### Precautionary statement

**Prevention**  
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

**Response**  
If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

**Storage**  
Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

### 3. Composition/information on ingredients

#### Substances

Chemical name	Common name and synonyms	CAS number	%
Toluene		108-88-3	100

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

#### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Provide oxygen, if available, or artificial respiration, if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a POISON CENTER or doctor/physician if you feel unwell.

#### Skin contact

Remove contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Wash clothing separately before reuse. Get medical attention if irritation develops or persists. Destroy or thoroughly clean contaminated shoes.

#### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

#### Ingestion

Call a physician or poison control center immediately. DO NOT INDUCE VOMITING. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.

#### Most important symptoms/effects, acute and delayed

Decrease in motor functions. Behavioral changes. Narcosis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain. Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.

#### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

#### Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>). Water may be an ineffective extinguishing medium.

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### Specific hazards arising from the chemical

Vapor may cause flash fire. Vapor is denser than air – flashback may be possible over considerable distances. The product can accumulate electrostatic charges, which may cause an electrical spark (ignition source).

#### Special protective equipment and precautions for firefighters

Firefighters must use full bunker gear including NIOSH-approved (or equal), full-face, self-contained breathing apparatus (SCBA) operated in positive pressure mode. Firefighters' protective clothing will provide only limited protection against liquid contact.

#### Fire fighting equipment/instructions

Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. Water spray should be used to cool structures and vessels. Use compatible foam to minimize vapor generation as needed. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Water runoff can cause environmental damage.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the SDS for Personal Protective Equipment.

# ASTRO PRODUCT CODE: 10306000

## Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Extinguish all flames in the vicinity. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Vapors may be controlled using a water fog. Remove with vacuum trucks or pump to storage/salvage vessels. Use explosion proof electric equipment.

Small Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. DO NOT use combustible materials such as sawdust. Use clean non-sparking tools to collect absorbed material.

Clean surface thoroughly to remove residual contamination. Retain all contaminated water for removal and treatment.

## Environmental precautions

Contain spillages with sand, earth or any suitable adsorbent material. Prevent entry into waterways, sewer, basements or confined areas. Do not allow material to contaminate ground water system. Reporting of releases to appropriate regulatory agencies may be required.

## 7. Handling and storage

### Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Consult with applicable standards such as NFPA 30, 'Flammable and Combustible Liquids Code'.

Before entering storage tanks and commencing any operation in a confined area, check the atmosphere for oxygen content and flammability. Use only with adequate ventilation. Wear personal protective equipment. Do not breath gas/vapor/spray. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash thoroughly after handling. Avoid release to the environment.

The product is highly flammable, and explosive vapor/air mixtures may be formed. Keep away from all ignition sources including heat, sparks and flame. Use non-sparking tools and explosion-proof equipment as applicable. This material is a static accumulator. Avoid accumulation of static charges during transfers in metallic systems. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. These alone may be insufficient to remove static electricity.

### Conditions for safe storage, including any incompatibilities

Flammable liquid storage. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. The pressure in sealed containers can increase under the influence of heat. Keep away from incompatible material. Keep away from food, drink and animal feedingstuffs.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Material	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

#### US. ACGIH Threshold Limit Values

Material	Type	Value
Toluene (CAS 108-88-3)	TWA	20 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Material	Type	Value
Toluene (CAS 108-88-3)	STEL	560 mg/m <sup>3</sup>
	TWA	150 ppm 375 mg/m <sup>3</sup> 100 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Material	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*

## ACGIH Biological Exposure Indices

Material	Value	Determinant	Specimen	Sampling Time
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

## Exposure guidelines

## US - California OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

## US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

**Appropriate engineering controls** Provide adequate general and local exhaust ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors and spray mist. Provide eyewash station and safety shower.

## Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses. If splash potential exists, wear full face shield and/or chemical goggles.

## Skin protection

**Hand protection** Chemical resistant gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

**Other** Wear chemical-resistant gloves, footwear and protective clothing appropriate for risk of exposure. Contact chemical protective clothing manufacturer for specific information. Flame retardant protective clothing is recommended.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. Protection provided by air-purifying respirators is limited and should not be used in atmospheres deficient in oxygen or where airborne concentrations are immediately dangerous to life or health.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

## Appearance

**Physical state** Liquid.

**Form** Liquid. Clear liquid with slight color.

**Color** Slight color.

**Odor** Characteristic, Toluene.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -139 °F (-95 °C) (as Toluene)

**Initial boiling point and boiling range** 231.08 °F (110.6 °C)

**Flash point** 39.2 °F (4.0 °C)

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not applicable.

## Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** 1.1 % (as Toluene)

**Flammability limit - upper (%)** 7.1 % (as Toluene)

**Vapor pressure** 21 mm Hg (as Toluene) (20°C)

**Vapor density** 3.1

# ASTRO PRODUCT CODE: 10306000

Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble in water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	896 °F (480 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Molecular formula	C7-H8
Molecular weight	92.14 g/mol
Oxidizing properties	Not oxidizing.

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May be fatal if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Behavioral changes. Decrease in motor functions. Narcosis. Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain. Edema.

### Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects.
----------------	---

Product	Species	Test Results
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	14.1 ml/kg
Inhalation		
LC50	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	No data available.	
Skin sensitization	No data available.	

<b>Germ cell mutagenicity</b>	No data available.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	Suspected of damaging the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs (central nervous system, kidney, peripheral nervous system) through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.
<b>Further information</b>	No other specific acute or chronic health impact noted.

## 12. Ecological information

<b>Ecotoxicity</b>	Toxic to aquatic life.
<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	The product is insoluble in water.
<b>Other adverse effects</b>	Oil spills are generally hazardous to the environment. The product contains volatile organic compounds which have a photochemical ozone creation potential.

## 13. Disposal considerations

<b>Disposal instructions</b>	Recover and recycle, if practical. Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. Do not allow this material to drain into sewers/water supplies.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 F

### US RCRA Hazardous Waste U List: Reference

Toluene (CAS 108-88-3)	U220
<b>Waste from residues / unused products</b>	Recover and recycle, if practical.
<b>Contaminated packaging</b>	Not applicable.

## 14. Transport information

### DOT

<b>UN number</b>	UN1294
<b>UN proper shipping name</b>	Toluene
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	IB2, T4, TP1
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	202
<b>Packaging bulk</b>	242

### IATA

<b>UN number</b>	UN1294
<b>UN proper shipping name</b>	Toluene
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-

**Packing group** II  
**Environmental hazards** No.  
**ERG Code** 3L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

**UN number** UN1294  
**UN proper shipping name** TOLUENE  
**Transport hazard class(es)**  
 Class 3  
 Subsidiary risk -  
**Packing group** II  
**Environmental hazards**  
 Marine pollutant No.  
**EmS** F-E, S-D  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
 Not established.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Toluene (CAS 108-88-3) LISTED

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**  
 Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical****SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Toluene	108-88-3	100

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Clean Water Act (CWA)** Hazardous substance  
**Section 112(r) (40 CFR 68.130)** Priority pollutant  
 Toxic pollutant

**Safe Drinking Water Act (SDWA)** 1 mg/l  
 1 mg/l

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) 35 %WV

## DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

## US state regulations

## US. Massachusetts RTK - Substance List

Toluene (CAS 108-88-3)

## US. New Jersey Worker and Community Right-to-Know Act

Toluene (CAS 108-88-3)

## US. Pennsylvania Worker and Community Right-to-Know Law

Toluene (CAS 108-88-3)

## US. Rhode Island RTK

Toluene (CAS 108-88-3)

## US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

## US - California Proposition 65 - Carcinogens &amp; Reproductive Toxicity (CRT): Listed substance

Toluene (CAS 108-88-3)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 08-May-2015

Revision date -

Version # 01

NFPA ratings



## Disclaimer

This Safety Data Sheet ("SDS") was prepared in accordance with 29 CFR 1910.1200 by PBF Holding Company LLC ("PBF"). PBF does not assume any liability arising out of product use by others. All risks of use of the product are assumed by the user. The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable and is offered in good faith. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations. WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted.